

WIRED CONFERENCE CONTROL SYSTEM

RD100 Controller - RD100C Chairman Unit - RD100D Delegate Unit



RD100 Controller

FEATURE

- With recording function, support Max.16G USB disk.
- The panel adopts buttons to control speaking mode and the number of speakers, breaking the traditional dial control.
- LED displays working mode and allowed speaking number.
- The number of speakers: 1, 3, 6 and full opening(4 forms can be chosen)
- Six meeting work modes:

1 CHAIRMAN MODE

2 FIRST IN FIRST OUT MODE

3 LAST IN FIRST OUT MODE

4 LIMIT MODE

5 FREE MODE

6 RESPONDER MODE

TECHNICAL PARAMETER

FREQUENCY RESPONSE:	AC 220V±10% 50HZ
RATED VOLTAGE:	100HZ-12.5HZ
OUTPUT IMPEDANCE:	REC: 200Ω LINE: 200Ω
BALANCE:	300Ω UNBALANCE: 400Ω
INPUT IMPEDANCE:	LINE:50KΩ PBIN: 50KΩ
S / N RATIO:	100DB (1KHZ THD1%)
SIZE:	480 * 44 * 220MM



RD100C Chairman unit

FEATURE

- With microphone, speaking button and indicator lamp that can show and control the state of speech.
- Whole plastic microphone shell.
- With a microphone unit connecting cable.
- Built-in speaker, equipped LCD screen show working state.
- With Chairman priority key; could shut all the delegate unit.
- The chairman unit can be placed in any position in loop.
- The chairman unit is unrestricted by the any function.
- The chairman unit quantity is unrestricted in the loop.
- Electronic key for adjust speaking volume and speaker volume.
- The power for units is supplied by the master controller at 9V safe voltage.
- Hand-in-hand connection method.
- With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER

TYPE:	CAPACITANCE
POLAR PATTERN:	ONE DIRECTION
FREQUENCY RESPONSE:	40HZ-16KHZ
SENSITIVITY:	-43±2DB@1KHZ
INPUT VOLTAGE:	DC 9V(POWERED BY HOST)
MIN INPUT IMPEDANCE:	1KΩ
S /N RATIO:	68DB(A)
OUTPUT CONNECTOR:	8P TERMINAL
INPUT AND OUTPUT WIRE:	2M 8P SHIELDED LINE
MICROPHONE LENGTH:	435MM
SIZE:	125*173*71MM
WEIGHT:	940G



RD100D Delegate unit

FEATURE

- With microphone, speaking button and indicator lamp that can show and control the state of speech.
- Whole plastic microphone shell.
- With a microphone unit connecting cable.
- Built-in speaker, equipped LCD screen show working state.
- Electronic key for adjust speaking volume and speaker volume.
- The power for units is supplied by the master controller at 9v safe voltage.
- Hand-in-hand connection method.
- With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER:

TYPE:	CAPACITANCE
POLAR PATTERN:	ONE DIRECTION
FREQUENCY RESPONSE:	40HZ-16KHZ
SENSITIVITY:	-43±2DB@1KHZ
INPUT VOLTAGE:	DC 9V(POWERED BY HOST)
MIN INPUT IMPEDANCE:	1KΩ
S /N RATIO:	68DB(A)
OUTPUT CONNECTOR:	8P TERMINAL
INPUT AND OUTPUT WIRE:	2M 8P SHIELDED LINE
MICROPHONE LENGTH:	435MM
SIZE:	125*173*71MM
WEIGHT:	940G