

WIRED CONFERENCE CONTROL SYSTEM

RD200 Controller || RD200C Chairman Unit || RD200D Delegate Unit



RD200 Controller

FEATURE:

- *It is a discussing and video-tracking wired conference system.
- *With recording function, support Max.16G USB disk.
- *The front panel adopts buttons to control speaking mode and the number of speakers, breaking the traditional dial control.
- *LCD screen displays working status
- *The number of speakers: 1, 2,3,4,5,6 and full opening
- *7 meeting work modes: ①chairman mode ②first in first out mode ③last in first out mode ④LIMIT mode ⑤FREE mode ⑥responder mode ⑦Apply speaking mode (just for some model unit)
- *The host can connect 60 microphone units, it divide into 4 parallel outputs, each channel can connect 20 units. It also able to connect expansion unit number of extended machine up to 255units
- *Equipped with audio parallel output and a 6.3 jack output, conference recording outputs and background music inputs interface.
- *Built-in telephone coupler input and output ports, and can be used for remote telephone conference. According to the principle of communication, it divide two-way telephone voice signals into inputs and outputs. In order to control the intercom setting of phone call and set aside between the hall.
- *RS232 interface can be achieved using computer software to control entire conference system function.
- *Designed with frequency shift feedback function, there is a key in the back panel.

TECHNICAL PARAMETER:

Frequency response: AC 220V±10% 50Hz

Rated voltage: 100Hz-12.5Hz

Output impedance: REC:200Ω LINE:200Ω

BALANCE: 300Ω UNBALANCE: 400Ω

Input impedance: LINE:50KΩ PBIN:50KΩ

S /N Ratio: 100dB (1KHz THD1%)

Size: 480*44*220 mm

Weight:6KG

RD200C Chairman unit



FEATURE:

- *With microphone ,speaking button and indicator lamp that can show and control the state of speech.
- *Plastic microphone cover shell and metal base.
- *With a microphone unit connecting cable.
- *Built-in speaker, equipped LCD screen show working state.
- *With Chairman priority key; could shut all the delegate unit.
- *The chairman unit can be placed in any position in loop.
- *The chairman unit is unrestricted by the any function.
- *The chairman unit quantity is unrestricted in the loop.
- *Electronic key for adjust speaking volume and speaker volume.
- *The power for units is supplied by the master controller at 9v safe voltage.
- *Hand-in-hand connection method.
- *With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER:

| |
|--|
| Type: capacitance |
| Polar pattern: one direction |
| Frequency response: 40Hz-16KHz |
| Sensitivity: -43±2dB@1KHz |
| Input voltage: DC 9V(powered by host) |
| Min input impedance: 1KΩ |
| S /N Ratio: 68dB(A) |
| Output connector: 8P terminal |
| Input and output wire: 2M 8P shielded line |
| Microphone length:435mm |
| Size::125*195*65mm |
| Weight:1300g |

RD200D Delegate unit



FEATURE:

- *With automatic video-tracking function.
- *With microphone ,speaking button and indicator lamp that can show and control the state of speech.
- *Plastic microphone cover shell and metal base.
- *With a microphone unit connecting cable.
- *Built-in speaker, equipped LCD screen show working state.
- *With Chairman priority key; could shut all the delegate unit.
- *The chairman unit can be placed in any position in loop.
- *The chairman unit is unrestricted by the any function.
- *The chairman unit quantity is unrestricted in the loop.
- *Electronic key for adjust speaking volume and speaker volume.
- *The power for units is supplied by the master controller at 9v safe voltage.
- *Hand-in-hand connection method.
- *With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER:

| |
|--|
| Type: capacitance |
| Polar pattern: one direction |
| Frequency response: 40Hz-16KHz |
| Sensitivity: -43±2dB@1KHz |
| Input voltage: DC 9V(powered by host) |
| Min input impedance: 1KΩ |
| S /N Ratio: 68dB(A) |
| Output connector: 8P terminal |
| Input and output wire: 2M 8P shielded line |
| Microphone length:435mm |
| Size::125*195*65mm |
| Weight:1300g |