

WIRED CONFERENCE CONTROL SYSTEM

RD300 Controller - RD300C Chairman Unit - RD300D Delegate Unit



RD300 Controller

FEATURE

- With recording function, support Max.16G USB disk.
- The panel adopts buttons to control speaking mode and the number of speakers, breaking the traditional dial control.
- LED displays working mode and allowed speaking number.
- The number of speakers: 1, 3, 6 and full opening(4 forms can be chosen)
- Six meeting work modes:

- | | |
|---------------------------|------------------|
| 1 CHAIRMAN MODE | 4 LIMIT MODE |
| 2 FIRST IN FIRST OUT MODE | 5 FREE MODE |
| 3 LAST IN FIRST OUT MODE | 6 RESPONDER MODE |

TECHNICAL PARAMETER

FREQUENCY RESPONSE:	AC 220V±10% 50HZ
RATED VOLTAGE:	100HZ-12.5HZ
OUTPUT IMPEDANCE:	REC: 200Ω LINE: 200Ω
BALANCE:	300Ω UNBALANCE: 400Ω
INPUT IMPEDANCE:	LINE:50KΩ PBIN: 50KΩ
S / N RATIO:	100DB (1KHZ THD1%)
SIZE:	480 * 44 * 220MM



RD300C Chairman unit

FEATURE

- With microphone ,speaking button and indicator lamp that can show and control the state of speech.
- Whole plastic microphone shell.
- With a microphone unit connecting cable.
- Single projection; With Anti-gas sonic boom and wind shield.
- With Chairman priority key; could shut all the delegate unit.
- The chairman unit can be placed in any position in loop.
- The chairman unit is unrestricted by the limiting function.
- The chairman unit quantity is unrestricted in the loop.
- High sensitivity microphone.
- High sensitivity microphone.
- The power for units is supplied by the master controller at 9 safe voltage.
- Hand-in-hand connection method.
- With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER

TYPE:	CAPACITANCE
POLAR PATTERN:	ONE DIRECTION
FREQUENCY RESPONSE:	40HZ-16KHZ
SENSITIVITY:	-43±2DB@1KHZ
INPUT VOLTAGE:	DC 9V(POWERED BY HOST)
MIN INPUT IMPEDANCE:	1KΩ
S / N RATIO:	68DB(A)
OUTPUT CONNECTOR:	8P TERMINAL
INPUT AND OUTPUT WIRE:	2M 8P SHIELDED LINE
MICROPHONE LENGTH:	425MM
SIZE:	132*150*58MM
WEIGHT:	500G



RD300D Delegate unit

FEATURE

- With microphone ,speaking button and indicator lamp that can show and control the state of speech.
- Whole plastic microphone shell .
- With a microphone unit connecting cable.
- Single projection; With Anti-gas sonic boom and wind shield.
- High sensitivity microphone.
- The power for units is supplied by the master controller at 9 safe voltage.
- Hand-in-hand connection method.
- With a microphone unit connecting cable 2m, 8P core line, convenient installation can increase efficiency.

TECHNICAL PARAMETER:

TYPE:	CAPACITANCE
POLAR PATTERN:	ONE DIRECTION
FREQUENCY RESPONSE:	40HZ-16KHZ
SENSITIVITY:	-45±2DB@1KHZ
INPUT VOLTAGE:	DC 9V(POWERED BY HOST)
MIN INPUT IMPEDANCE:	1KΩ
S / N RATIO:	68DB(A)
OUTPUT CONNECTOR:	8P TERMINAL
INPUT AND OUTPUT WIRE:	2M 8P SHIELDED LINE
MICROPHONE LENGTH:	425MM
SIZE:	132*150*58MM
WEIGHT:	500G