

Professional speaker system

RD 104T

Two-way loudspeaker system



The RD 104T is a highly weather-resistant, single 4" 2-way full range loudspeaker, the body is made of engineering plastic injection molding. fitted with one 4" mid-woofer and one 0.8" dome tweeter. The system conforms to IP46 international standard.RD 104T is equipped with multi-tap transformer based on RD 104.

Features:

- ₩ Highly weather-resistant IP46 rating
- **※** Engineering plastic injection molding

Applications:

- **※** Good used for meeting rooms, shops, water parks
- **※** Outdoor background music, swimming pools

Technical specifications:

FREQUENCY RESPONSE	75 Hz-20kHz(-3dB)
DRIVERS	1×4 "(100mm)/1"voice coil LF
	1×0.8 "(20mm) / dome tweeter
INPUT VOLTAGE	100V
POWER	10W/20W/40W/OFF/16Ω
SENSITIVITY	88dB 1watt/1 metre
MAXIMUM SPL	104dB continuous,110 dB peak
IMPEDANCE	16 ohms nominal
DISPERSION(-6dB)	120 ° ×90 °
CROSSOVER	3.5kHz passive
DIMENSIONS	(W) 141mm $\times(D)$ 170mm $\times(H)$ 230mm
WEIGHT	3 kg/pc

Overall dimensions







