

Ture Diversity Wireless Microphone

The true diversity antenna design guarantees extremely high stability and clear sound quality. Two-way shuttle knob which bring simple operation. In short, the perfect combination of appearance and strength makes it is the best choice for live performance.

Wireless Receiver RD-300WM

- Carrier frequency Range: UHF 500MHz~670MHz
- Modulation: FM
- Oscillation Mode: PLL
- Max Deviation: $\pm 45\text{kHz}$
- S/N Ratio: $>105\text{dB}$
- Frequency Response: $45\text{Hz} - 18\text{kHz} \pm 3\text{dB}$
- T.H.D: $<0.7\% @ 1\text{kHz}$
- Power: DC12-16V
- Effective Distance: 300 meters
- RD-300WM: Dual-Channel



RD-300WM

Transmitter Unit

- Carrier frequency Range: UHF 500MHz~670MHz
- Oscillation Mode: PLL
- Harmonic Radiation: $<-65\text{dBm}$
- Max Deviation: $\pm 45\text{kHz}$
- Capsule: Dynamic
- Frequency Response: $45\text{Hz} - 18\text{kHz} \pm 3\text{dB}$
- RF Power Output: 10MW
- Consumption: $<90\text{mA}$
- Power: 2 x AA battery

