

Professional speaker system

RD 106T

Two-way loudspeaker system



The RD 106T is a highly weather-resistant, single 6" 2-way full range loudspeaker, the body is made of engineering plastic injection molding. fitted with one 6" mid-woofer and one 1" HF driver. The system conforms to IP46 international standard. RD 106T is equipped with multi-tap transformer based on RD 106.

Features:

- ₩ Highly weather-resistant IP46 rating
- **※** Engineering plastic injection molding

Applications:

- **※** Good used for meeting rooms, shops, water parks
- **※** Outdoor background music, swimming pools

Technical specifications:

EDEOLIENGY DEGDONGE	(0.11 401.11 (0.1D)
FREQUENCY RESPONSE	60 Hz-18kHz(-3dB)
DRIVERS	1×6"(150mm)/1.5"voice coil LF
	$1\times1"(25\text{mm}) / 1"\text{voice coil HF}$
INPUT VOLTAGE	100V
POWER	20W/40W/80W/OFF/16Ω
SENSITIVITY	89dB 1watt/1 metre
MAXIMUM SPL	108dB continuous,114 dB peak
IMPEDANCE	16 ohms nominal
DISPERSION(-6dB)	90 ° ×60 °
CROSSOVER	2.4kHz passive
DIMENSIONS	(W)182mm×(D)224mm×(H)362mm
WEIGHT	6 kg/pc

Overall dimensions







