

# Professional speaker system

## **RD 108T**

Two-way loudspeaker system



The RD 108T is a highly weather-resistant, single 8" 2-way full range loudspeaker, the body is made of engineering plastic injection molding. fitted with one 8" mid-woofer and one 1" HF driver. The system conforms to IP46 international standard. RD 108T is equipped with multi-tap transformer based on RD 108.

#### Features:

- \* Highly weather-resistant IP46 rating
- Engineering plastic injection molding

## **Applications:**

- Full range sound reinforcement, confence system;
- \* Background music or other public places
- Outdoor background music, water parks and swimming pools

### **Technical specifications:**

| FREQUENCY RESPONSE | 60 Hz-18kHz(-3dB)                          |
|--------------------|--|
| DRIVERS            | 1×8"(200mm)/2"voice coil LF                |
|                    | 1×1"(25mm) /1"voice coil HF                |
| INPUT VOLTAGE      | 100V                                       |
| POWER              | 37.5W/75W/150W/OFF/16Ω                     |
| SENSITIVITY        | 94 dB 1W/1M                                |
| MAXIMUM SPL        | 116 dB continuous,122 dB peak              |
| IMPEDANCE          | 16 ohms nominal                            |
| DISPERSION(-6dB)   | 90 ° ×50 °                                 |
| CROSSOVER          | 2.3kHz passive                             |
| DIMENSIONS         | $(W)241mm \times (D)285mm \times (H)450mm$ |
| WEIGHT             | 10Kg/pc                                    |

#### **Overall dimensions**







